

Flexible heating films

Engineering review and quotation note | Revision 2026-10-15

Custom carbon or conductive-pattern heating elements for a defined mounting area. Review the available voltage, required heating area, bonding surface and lead-wire route together.

The installed temperature depends on the mounting stack, heat loss, sensor position and control electronics. Agree the power limits, protection requirements and sample acceptance criteria with the equipment team.



Heating-element sample with a patterned surface, lead wire and connector. No thermal output or safety approval is established by this photograph.

Use this note with the current drawing and equipment requirements. It is not a fixed performance specification, test report or finished-equipment approval.

Construction and scope review

Item	Options / Description
Product Type	Flexible heating film, carbon heating element, custom thermal management film
Material	PET or PI base film, selected according to application requirement
Heating Layer	Carbon or conductive ink heating pattern
Thickness	Confirm the total stack thickness on the project drawing
Voltage	Low voltage or custom voltage based on heating area and power design
Temperature Range	Application dependent, confirmed by structure and control design
Heating Mode	Uniform heating or zoned heating layout
Efficiency	Power use depends on resistance, voltage, mounting conditions and control duty
Adhesive	3M or industrial adhesive, selected according to bonding surface
Applications	EV, medical, industrial, automotive seat heating, smart wearable and consumer electronics

Final specifications depend on heating area, voltage, target temperature, installation surface, control method and operating environment.

Mounted-sample review

For energy-storage cabinets, charging equipment, outdoor terminals and instruments, the heating film should be placed where it solves a defined function: clearing condensation from a window, warming a seal path, stabilizing a sensor area, or helping a local module recover after the first shift starts.

Decision	What buyers should confirm
Heat target	Window, seal, connector area, sensor pocket, battery-adjacent surface or user-contact zone.
Mounting surface	Metal, plastic, glass, fabric or coated housing surface, including flatness and adhesive compatibility.
Control method	Open-loop power, thermostat, NTC feedback or equipment-side controller with safe temperature limits.
Failure risk	Hot spots, poor adhesion, cable strain, moisture at the edge, over-heating of nearby plastic, or slow recovery because the film is placed too far from the cold point.

When the project involves a cabinet, door or sealed enclosure, include a simple section view in the RFQ so the heating area, adhesive layer, lead exit and sensor position can be checked before tooling.

Agree the scope of any inspection records, test conditions and acceptance criteria before sampling. A company certificate does not replace approval of the actual component in the intended equipment.

Prepare your quotation

To help us review the heating film structure and provide a practical quotation, please send available project information.

- 2D drawing, 3D file, target shape or mounting area
- Required voltage, resistance, power or target temperature if known
- Heating area, uniformity requirement and possible zoned heating layout
- Base material preference such as PET or PI
- Adhesive, insulation, waterproof or protection requirement, including the exact mounting surface
- Connector, lead wire, strain relief and temperature sensor requirement
- Application environment, cold-start condition, operating time and control method
- Prototype quantity, annual quantity and target lead time

[Request a Quote](#) | [Current product page](#)

Shenzhen Baoshengda Technology Co., Ltd. | szbld@vip.163.com